Notes: (Unless Otherwise Specified)

1. Waterproof Rate: IP67.
2. Suitable Cable OD=5.0mm To 6.0mm.
3. Recommend Housing Torque: 6~7 Kgf-cm.
4. Recommend Gland Nut Torque: 9~10 Kgf-cm.
5. RoHS Compliant.

REV	ECN#	DESCRIPTION OF REVISION	DRAW BY DATE	CHECK BY DATE	APPROVE BY DATE
A0		Mass Production	Lucas 02/19/13	Ray 02/19/13	Ray 02/19/13



GTC
DOC.CENTER.ISSUE
FEB.19.2013
ONLY FOR RELEASE

Item	Part Name	Material / Finish	Q'ty
9	Base	Thermoplastic Color: Black	1
8	Gland Nut	Thermoplastic Color: Black	1
7	Cage	Thermoplastic Color: White	1
6	Gland	Silicone Color: Green	1
5	Cover	Thermoplastic Color: Black	1
4	Gasket	Silicone Color: Black	1
3	Contacts	Copper Alloy Finish: Au Plated	10
2	O-Ring	Silicone Color: Red	1
1	Housing	Thermoplastic Color: Black	1



Pin Assignment



TITLE	DRAWING NUMBER	REV.
C2 2A 10P Field Installable Cable To Cable Male Crimp Lock	GT152294-21100	A0

DO NOT SCALE DRAWINGS	B	N/A	Lucas 02/19/13	Ray 02/19/13	Ray 02/19/13	X.X ± 0.5 X.XX ± 0.2 X.XXX ± 0.05 ANGLES ± 1°	mm	1/1
THIRD ANGLE PROJECTION	SIZE	SCALE	DRAW / DATE	CHECK / DATE	APPROVE / DATE	TOLERANCES	UNIT	SHEET

GT Contact CO.,LTD

NOTICE OF PROPRIETARY PROPERTY:

THE INFORMATION CONTAINED HEREIN IS THE PROPRIETARY PROPERTY OF GT Contact CO.,LTD THE POSSESSOR AGREES TO THE FOLLOWING:
(i) TO MAINTAIN THIS DOCUMENT IN CONFIDENCE
(ii) NOT TO REPRODUCE OR COPY IT
(iii) NOT TO REVEAL OR PUBLISH IT IN WHOLE OR PART
(iv) ALL RIGHTS RESERVED