



Note:

1. Waterproof Rate: IP68.
2. Durability: 100 Cycles Min.
3. DWV: 650 Vrms.
4. Rated Voltage: 30V AC/DC.
5. Insulation Resistance: 100 MΩ Min.
6. RoHS Compliant.

REV	ECN#	DESCRIPTION OF REVISION	DRAW BY DATE	CHECK BY DATE	APPROVE BY DATE
A0		Mass Production	Viola 04/16/18	Lucas 04/16/18	Ray 04/16/18



1	Black	1
2	Orange	2
3	Brown	3
4	Red	4
5	Yellow	5

Wiring Diagram



Part No.	Cable Length	Tol.
GT2322K5-23051-10	10000 mm	+500
GT2322K5-23051-09	9000 mm	+450
GT2322K5-23051-08	8000 mm	+400
GT2322K5-23051-07	7000 mm	+150
GT2322K5-23051-06	6000 mm	+150
GT2322K5-23051-05	5000 mm	+150
GT2322K5-23051-04	4000 mm	+150
GT2322K5-23051-03	3000 mm	+100
GT2322K5-23051-02	2000 mm	+100
GT2322K5-23051-01	1000 mm	+50
GT2322K5-23051-Z9	900 mm	+50
GT2322K5-23051-Z8	800 mm	+50
GT2322K5-23051-Z7	700 mm	+50
GT2322K5-23051-Z6	600 mm	+50
GT2322K5-23051-Z5	500 mm	+50
GT2322K5-23051-Z4	400 mm	+50
GT2322K5-23051-Z3	300 mm	+25
GT2322K5-23051-Z2	200 mm	+25
GT2322K5-23051-Z1	100 mm	+25

Item	Part Name	Material / Finish	Q'ty
2	Cable	UL2464 22AWG*5C+Talc(UV) Color: Black, DD=5.5±0.2mm	1
1	M8 B-Coding 3A 5P Cable End 90° Female	GT Contact P/N: GT232225-23051-XX	2

TITLE						DRAWING NUMBER			REV.
M8 B-Coding 3A 5P Cable End 90° Female Twin-Head With Cable						GT2322K5-23051-XX			A0
THIRD ANGLE PROJECTION	SIZE	SCALE	DRAW / DATE	CHECK / DATE	APPROVE / DATE	TOLERANCES		UNIT	SHEET
	B	1.5:1	Viola 04/16/18	Lucas 04/16/18	Ray 04/16/18	X.X ± 0.5 X.XX ± 0.2	X.XXX ± 0.05 ANGLES ± 1°	mm	1/1

GT Contact CO.,LTD

NOTICE OF PROPRIETARY PROPERTY:
THE INFORMATION CONTAINED HEREIN IS THE PROPRIETARY PROPERTY OF GT Contact CO.,LTD THE POSSESSOR AGREES TO THE FOLLOWING:
(i) TO MAINTAIN THIS DOCUMENT IN CONFIDENCE
(ii) NOT TO REPRODUCE OR COPY IT
(iii) NOT TO REVEAL OR PUBLISH IT IN WHOLE OR PART
(iv) ALL RIGHTS RESERVED